



Economic Benefits of Higher Enriched Assays for 24-Month Cycle Length

Coral Kazaroff, Andrew Johnson,
Dan Kotlyar

Date: 10/15/2019

Background and Objectives

Background:

- The current fuel enrichment is restricted to 5% in commercial LWRs
- The fuel cycle length is typically between 12 to 18 months

Objectives:

- Examine enrichment required to extend cycle length to 24 months
- Assess economic benefit or penalty

Constraints


- Limiting pin burnup
 - Accident-tolerant fuels
 - Limit of 62 → possible shift
- Increase fuel enrichment to align with industry efforts
- Maintain reactivity control requirements
 - Burnable poison design
 - Critical boron concentration (CBC)

General Approach and Model


- 17x17 PWR
 - Varying enrichments from 4.0 w/o through 6.7 w/o
 - Gadolinia (Gd_2O_3) burnable absorbers
- 3-batch management scheme for full-core analysis
 - 80 fresh, 80 once-burned, 33 twice-burned
- For each enrichment, use NLRM to obtain
 - Core reactivity
 - Core boron worth
 - Critical boron concentration

Fuel Assembly Configurations


8 BP




20 BP



24 BP




32 BP



U235 wt%	Gad wt%	# Burnable Pins
4	6	8
4.45	6	12
4.9	6	16
5.35	8	20
5.8	8	24
6.25	8	28
6.7	8	32

$\text{Gd}_2\text{O}_3 + \text{UO}_2$

Methodology



Non-Linear Reactivity Model (NLRM)

$$\rho(t) = a_0 + a_1 t + a_2 t^2 + a_3 t^3$$

- The discrete points of reactivity vs. time are fitted into a polynomial
 - Burnable absorbers make reactivity non-linear; in our case this was the most suitable polynomial
- The first points are not used for the fitting procedure
- Using the polynomial and leakage assumption, the cycle length T_c can be evaluated:

$$\frac{80 \times \rho(1T_c) + 80 \times \rho(2T_c) + 33 \times \rho(3T_c)}{193} = 0.03$$



Core Reactivity Estimation

$$\rho_{core}(t) = \frac{1}{N} \sum_{i=0} N_i \rho(t + iT_c) - \rho_L$$



- A **three-batch** scheme was adopted ($0 \leq i \leq 2$)
- N – total number of fuel assemblies
- $\rho(t + iT_c)$ - reactivity of the fuel assembly at different time
- T_c is the cycle length (days) that is iteratively calculated
- ρ_L - leakage (assumed as 3%)
- Similar procedure for boron worth

$$BW_{core}(t) = \frac{1}{N} \sum_{i=0}^{N-1} N_i \cdot BW(t + iT_c)$$

Assembly and Core Reactivity




Boron Worth and CBC



Cycle Length

- Fit enrichment to cycle length
- 4.27 w/o → 18 month cycle length
- 6.13 w/o → 24 month cycle length



Fuel Cycle Costs per kg U

Process	4.27 wt% U235		6.13 wt% U235	
	Requirement	Cost	Requirement	Cost
U3O8	8 kg	451.80	11.6 kg	659.00
Conversion	8.0 kg	117.40	11.6 kg	171.20
Enrichment	7.2 SWU	307.60	11.5 SWU	495.20
Fabrication		400.0		400.0
Total		1276.90		1725.50

Economic Analysis

- Compute total fuel cost per kg-U
- Compute fuel and outage costs per ¢/kWh_e

- Fuel costs =

$$\frac{\text{Total cost of outage}}{\text{Power} \times T_c \times \eta} \left[\frac{\text{¢}}{\text{kWh}_e} \right]$$



- Outage costs = $\frac{P_T}{B_d \times \eta} \left[\frac{\text{¢}}{\text{kWh}_e} \right]$

Parameter	Value
Uranium ore, \$/kg	56.80
Conversion , \$/kg	\$14.75 /kgU
SWU , \$	\$43.00
Fabrication , \$/kg	\$400.00 /kgU
Electric efficiency	34%
Fixed outage cost, \$	\$30 million

Economic Results

Parameter	Value – 4.27 wt%	Value – 6.13 wt%
Cycle length	18 mo	24 mo
Assembly burnup [GWd/MTU]	46.8	63.5
Max pin burnup [GWd/MTU]	56.2	76.1
Fuel cost, [<i>cent/kWh_e</i>]	0.334	0.333
Outage cost, [<i>cent/kWh_e</i>]	0.204	0.150
Fuel cycle cost, [<i>cent/kWh_e</i>]	0.538	0.484 [-10 %]

Limiting Pin Burnup



- Pin burnup < 62 GWd/tU, but keep 6.13 enriched fuel
- Vary number of fuel assemblies
- Two-batch system keeps burnup below 62

Summary

- Fuel cycle analysis with higher enrichments
 - Single assembly, non-linear reactivity → full core
- Recover near-standard 18 mo cycle with 4.27 wt% enrichment
- Obtain 24 month cycle with 6.13 wt% enrichment
- Potential fuel cycle cost savings of 10%
- ATF progress, NRC licensing

Future Work

- 3D full-core analysis
- Optimize loading pattern with enrichment and gadolinia configurations

Acknowledgements

The authors would like to thank Framatome, Inc. for sponsoring this work and providing guidance and data

Thank you very much!

Questions?

coralkazaroff12@gatech.edu

ajohnson400@gatech.edu

dan.kotlyar@me.gatech.edu